

EVENT REMOTE CONSOLE FOR UP TO 3 GRAPHIC SWITCHER II™

FOR SIMULTANEOUS CONTROL OF UP TO 3 UNITS

REMOTE CONSOLE Ref. RCU2811



REFERENCE:

- RCU2811

FEATURES:

- 3 simultaneous effects
- Fast Access settings
- Easy Control of every functions
- Rackable

DESCRIPTION :

With only one device, the “**REMOTE CONTROL**”, ref. **RCU2811**, you can control up to 3 Graphic Switcher II™ (ref. GSW2811R) at the same time. You can then display up to 48 sources upon 3 screens. For your presentation, all of the Sequences & effects of the Graphic Switcher II™ (Cut, Fade, Title Effect, Wipes) can be synchronized or separately activated (automatically or thanks to the T-BAR).

As the Graphic Switcher II™, the Remote Control Unit™ is very easy to use and to connect. The unit can be integrated in any control room's 19" rack .

TECHNICAL SPECIFICATIONS :

USER'S CONTROLS:

- PROGRAM: MAIN bus of output with 16 Input Control Keys and 1 Black Control Key
- PRESET: PREVIEW bus with 16 Input Control Keys for Selection and 1 Black Control Key
- FRAME FREEZE: Control key + Led
- CUT: Control Key for Seamless Switching between PROGRAM / PRESET
- TAKE: Control Key for Effect (Fader) Switching between PROGRAM / PRESET
- STEP: Control key for step sequence switching (Pre-programmed)

- FADER EFFECT: 3 Control Keys for Selection of the Switching Effect: WIPE, FADE, TITLE
- ADJUST: Image adjustment of each Input:
 - Horizontal and Vertical position and size adjustment
 - Recall of previous image setting
 - Store function for memorization of the format and image setting
- SWITCHER SELECT (1, 2, 3): 3 control keys for selection of the Graphic Switcher II™ to be controled
- T-BAR: Lever for Manual Fade control

LCD WINDOW & CONTROL BUTTONS FOR:

- Input Format Status
- Output Format & Sync.Selection
- Switching Effect Selection
- Contrast & Black Level, R,G,B, Color, Hue, Brightness, Sharpness, Gamma Adjustments
- Test Pattern
- H & V Smoothing Filter
- Front Panel & Control Key Lock out

CONNECTORS:

- INPUT: 3 x RS-232 Connector (DB9 male) for connecting up to 3 GSW2811R

DIMENSIONS:

- 5U, 19"
- D 220 x W 446 x H 100 mm
D 8.7" x W 17.5" x H 3.9"

WEIGHT: 4 kg / 8.8 Lbs

POWER SUPPLY:

- Internal, Universal, Automatic 100 - 250 VAC; 50 / 60 Hz (25 W) (UL, CSA, CE, IEC 950)

SUPPLIED WITH:

- 1 x AC Power Cable
- 3 x Remote Cables DB9 (M/F) (3 m / 10 ft)

WARRANTY:

3 years warranty on Parts & Labor, back to the factory

ACCESSORIES REFERENCES (optional) :

- **10109** : DB9 (M/F)
Remote cable (0,5 m - 1.6 ft)
- **10110** : DB9 (M/F)
Remote cable (3 m - 10 ft)

- **10111** : DB9 (M/F)
Remote cable (5 m - 16 ft)
- **10112** : DB9 (M/F)
Remote cable (10 m - 33 ft)

- **10113** : DB9 (M/F)
Remote cable (20 m - 66 ft)
- **10114** : DB9 (M/F)
Remote cable (30 m - 100 ft)

- Special length cables available upon request, see Cables section (**HQRS Cable**).